

FUEL TANK SENDERS

Mechanical Spiral Contents Gauge

The gauge is of rugged construction and is designed to be fitted onto the top surface of a tank with an 1 1/2" BSP thread.

Stock held:

20-60cm in 5 cm increments Ref: FOZ

Fozmula fitting flange available Ref: FOZFLANGE

Sensotex

The **SFW** range of fuel senders comprise of a stainless steel shaft and housing. Inside the sealed shaft are 10 miniature reed switches which are activated by a magnet contained within the float.

Fitting thread - 1 1/4" BSP with O ring.

Stock held:

20-60cm in 5 cm increments Ref: SFW-02E

Fitting flange available Ref: SA-01
Only available in European specification (0-180 Ω).

Wema

The **S3** series of fuel senders comprise of a stainless steel shaft and housing. Inside the sealed shaft are 10 miniature reed switches which are activated by a magnet contained within the float.

These units have proven to be extremely reliable and are our best selling senders.

These senders are used by Fairline, Princess and many other large boatbuilders.

The sender is supplied to suit the depth of the tank. Fitting is as easy as screwing in the sender and joining two wires to the gauge.

Fitting thread - 1 1/4" BSP with O ring.

Stock held:

S3 20-60cm in 5cm increments Ref: S3

Longer lengths are available to special order.

Fitting flange (for VDO replacement senders) Ref: FL-2
Fitting flange (for new tanks) Ref: FL-3

Available in European specification (0-180 Ω).
This output will match our Analogue Gauges.

US specification (230-40 Ω) available as special order.

FOZMULA



SENSOTEX



WEMA



TEK TANKS

The Old Stables, West End Farm, Upper Froyle, Alton, Hampshire GU34 4JR. England
Tel: +44 (0)1420 520830 fax: +44 (0)1420 520840 email: sales@tek-tanks.com
www.tek-tanks.com

TEK TANKS
Water Waste and Fuel